



THOMSON - GORDON LTD

THOMSON-GORDON LIMITED

3225 Mainway, Burlington, Ontario - Canada L7M 1A6

Phone: 905-335-1440 / Fax: 905-335-4033

THORLUBE

THORCLEAN

SUPER PREMIUM SYNTHETIC
COMPRESSOR LUBRICANTS

THORLUBE - THORCLEAN

THORCLEAN compressor cleaner is a NON-Toxic / NON-Hazardous compressor cleaner that is safe to use in all compressor applications. It is intended to replace the existing compressor fluid to clean and remove varnish and carbon deposits while the compressor operates.

THORCLEAN can be run in a varnished compressor for at least 2000 hours. THORCLEAN should be sampled after 200 hours and then every 400 hours in badly varnished compressors. Increased filter and separator replacement may result during the cleaning process.

- Safe Non-Toxic Cleaner
- Excellent Dispersant Properties
- High Flash & Auto Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Replaces Compressor Fluid - Compressor Runs Normally
- Long Cleaner Fluid Life
- Excellent Rust Control
- Solubilizes Carbon and Varnish
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption

Typical Properties

Lubricant Designation	THORCLEAN
Viscosity Index	64
Viscosity cSt @ 40 °C	46
Viscosity cSt @ 100 °C	5.9
Viscosity SUS @ 100 °F	214
Viscosity SUS @ 212 °F	45.3
Flash Point °F	448
Auto-Ignition Point °F	782
Pour Point °F	-50
Four Ball, 40 Kg, 1200 RPM, 167°F	
1 Hr, Scar Dia mm	.40
Four Ball Weld Point, Kg	100
Copper Corrosion, 24 Hr	1a
Demulsibility, 130 °F, 30 min	40/38/2