



THOMSON - GORDON LTD

THOMSON-GORDON LIMITED

3225 Mainway, Burlington, Ontario - Canada L7M 1A6

Phone: 905-335-1440 / Fax: 905-335-4033

ATP

**SUPER PREMIUM
SYNTHETIC AIR TOOL
PROTECTOR**

ATP

THOMSON GORDON's ATP is a super premium, synthetic air tool lubricant. It is made from advance technology synthetic base and blended with the finest additives to provide maximum lubrication, cleaning, and protection for modern air tools.

THOMSON GORDON's ATP removes deposits and cleans stuck air tools. It provides outstanding service in even the most severe operating conditions.

- Outstanding Oxidation Stability
- Unsurpassed Water Separation
- High Flash & Auto-Ignition Points
- Low Volatility
- Very High Film Strength
- Excellent Coolant Properties
- Excellent Cleaning Properties
- Superior Penetrating Ability
- Excellent Rust Control
- Carbon and Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption

Typical Properties

Lubricant Designation	ATP
Viscosity Index	127
Viscosity cSt @ 40 °C	22
Viscosity cSt @ 100 °C	4.6
Viscosity SUS @ 100 ° F	106.3
Viscosity SUS @ 212 ° F	41.4
Flash Point °F	315
Auto-Ignition Point °F	655
Pour Point °F	-20
Oxidation Stability	4000
Color	<.5
Copper Corrosion, 24 Hr	1a
Rust Test	No Rust
Demulsibility, 130 °F, 30 min	40/40/0