



# THOMSON - GORDON LTD

THOMSON-GORDON LIMITED

3225 Mainway, Burlington, Ontario - Canada L7M 1A6  
Phone: 905-335-1440 / Fax: 905-335-4033

## THORLUBE SERIES 2 3202-P, 4602-P, 6802-P

SUPER PREMIUM SYNTHETIC  
COMPRESSOR LUBRICANTS

## THORLUBE SERIES 2

THORLUBE SERIES 2 compressor lubricants represent Thomson Gordon's continued leadership in producing exceptional performance compressor fluids. These are blended from several synthetic base stocks, have a new advanced technology additive system, and provide outstanding performance. THORLUBE SERIES 2 lubricants combine the best characteristics of these base stocks to form a synergistic blend of fluids and additive systems.

- Outstanding Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Very Long Life Fluid
- Energy Savings
- Carbon and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Excellent Materials Compatibility
- Reduced Lubricant Consumption
- Excellent Rust & Corrosion Control

### Typical Properties

| Lubricant Designation             | 3202-P  | 4602-P  | 6802-P  |
|-----------------------------------|---------|---------|---------|
| Viscosity Index                   | 128     | 130     | 131     |
| Viscosity cSt @ 40 °C             | 34      | 49      | 69.8    |
| Viscosity cSt @ 100 °C            | 6.1     | 7.9     | 10.2    |
| Viscosity SUS @ 100 ° F           | 159.0   | 228     | 323.8   |
| Viscosity SUS @ 212 ° F           | 45.9    | 52.0    | 59.9    |
| Flash Point °F                    | 440     | 450     | 465     |
| Auto-Ignition Point °F            | 735     | 785     | 790     |
| Pour Point °F                     | -48     | -38     | -32     |
| Four Ball, 40 Kg, 1200 RPM, 167°F |         |         |         |
| 1 Hr, Scar Dia mm                 | .40     | .40     | .40     |
| Four Ball Weld Point, Kg          | 100     | 100     | 120     |
| Copper Corrosion, 24 Hr           | 1a      | 1a      | 1a      |
| Demulsibility, 130 °F, 30 min     | 40/40/0 | 40/40/0 | 40/40/0 |