



THOMSON - GORDON LTD

THOMSON-GORDON LIMITED

3225 Mainway, Burlington, Ontario - Canada L7M 1A6
Phone: 905-335-1440 / Fax: 905-335-4033

THORLUBE SERIES 4

3204-S, 4604-S,
10004-S, 15004-S

SUPER PREMIUM SYNTHETIC
COMPRESSOR LUBRICANTS

THORLUBE SERIES 4

THORLUBE SERIES 4 compressor lubricants are premium, semi-synthetic compressor lubricants with an advanced technology additive system. They are blended from the finest semi synthetic materials available. Proven in countless millions of horsepower hours of service in almost every type of compressor made.

THORLUBE SERIES 4 compressor lubricants give outstanding service, even in moderately severe operating conditions.

- Good Oxidation Stability
- High Viscosity Index
- High Flash & Auto Ignition Points
- Low Volatility
- Good Film Strength
- Excellent Coolant Properties
- Energy Savings
- Good Fluid Life
- Excellent Rust Control
- Good Carbon and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption

Typical Properties

Lubricant Designation	3204-S	4604-S	10004-S	15004-S
Viscosity Index	110	105	102	124
Vis cSt @ 40 °C	38.1	46.0	100.1	149.1
Vis cSt @ 100 °C	6.2	6.9	11.5	17.1
Vis SUS @ 100 °F	178.1	218.8	472.7	704.0
Vis SUS @ 212 °F	46.5	48.8	64.6	86.4
Flash Point °F	447	440	465	517
Auto-Ignition Point °F	757	767	786	839
Pour Point °F	-36	-30	-29	-15
Four Ball, 40 Kg, 1200 RPM, 167 °F 1 Hr, Scar Dia mm	.46	.45	.44	.40
Four Ball Weld point, Kg	100	100	100	100
Copper Corrosion, 24 Hr.	1a	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/0	40/40/0